

# EVOX



## 1600.1 EVOX

### 1Ω

POWER @ 4Ω: 1 X 657 WRMS  
POWER @ 2Ω: 1 X 1056 WRMS  
POWER @ 1Ω: 1 X 1600 WRMS  
OPERATING VOLTAGE: 8V - 16V  
CURRENT DRAW (MUSIC): 62A  
CURRENT DRAW (MAX): 125A  
RECOMMENDED FUSE (MUSIC): 70A  
TOTAL EFFICIENCY: 89%  
DAMPING FACTOR: >2000  
FREQUENCY RESPONSE (-3DB): 5HZ - 25KHZ  
SNR: 94DB  
CROSSOVER LPF: 50HZ - 500HZ  
SUBSONIC: 5HZ - 30HZ  
THD + N (10% RATED POWER): 0.1%

### 2Ω

POWER @ 4Ω: 1 X 1056 WRMS  
POWER @ 2Ω: 1 X 1600 WRMS  
POWER @ 1Ω: 1 X N/A  
OPERATING VOLTAGE: 8V - 16V  
CURRENT DRAW (MUSIC): 62A  
CURRENT DRAW (MAX): 125A  
RECOMMENDED FUSE (MUSIC): 70A  
TOTAL EFFICIENCY: 89%  
DAMPING FACTOR: >2000  
FREQUENCY RESPONSE (-3DB): 5HZ - 25KHZ  
SNR: 94DB  
CROSSOVER LPF: 50HZ - 500HZ  
SUBSONIC: 5HZ - 30HZ  
THD + N (10% RATED POWER): 0.1%



CEA 2006  
COMPLIANT

