

EVOX



3000.1 EVOX

1Ω

POWER @ 4Ω: 1 X 1307 WRMS
POWER @ 2Ω: 1 X 1980 WRMS
POWER @ 1Ω: 1 X 3000 WRMS
OPERATING VOLTAGE: 8V - 16V
CURRENT DRAW (MUSIC): 121A
CURRENT DRAW (MAX): 242A
RECOMMENDED FUSE (MUSIC): 140A
TOTAL EFFICIENCY: 86%
DAMPING FACTOR: >2000
FREQUENCY RESPONSE (-3DB): 5HZ - 25KHZ
SNR: 90DB
CROSSOVER LPF: 50HZ - 500HZ
SUBSONIC: 5HZ - 30HZ
THD + N (10% RATED POWER): 0.1%

2Ω

POWER @ 4Ω: 1 X 1980 WRMS
POWER @ 2Ω: 1 X 3000 WRMS
POWER @ 1Ω: 1 X N/A
OPERATING VOLTAGE: 8V - 16V
CURRENT DRAW (MUSIC): 121A
CURRENT DRAW (MAX): 242A
RECOMMENDED FUSE (MUSIC): 140A
TOTAL EFFICIENCY: 86%
DAMPING FACTOR: >2000
FREQUENCY RESPONSE (-3DB): 5HZ - 25KHZ
SNR: 90DB
CROSSOVER LPF: 50HZ - 500HZ
SUBSONIC: 5HZ - 30HZ
THD + N (10% RATED POWER): 0.1%



CEA 2006
COMPLIANT



SOUNDIGITALUSA



SOUNDIGITALUSA

YOUR MUSIC. YOUR POWER.

